



THREAD-ON UNIVERSAL SD HOUSINGS

Compatible With Subsite®, DigiTrak™ & Underground Magnetics™.



Universal Housings - Fits Most 2-cell & 4-cell Subsite, U-Mag or DigiTrak Transmitters

Drill Rig Thrust	Diameter	Thread (rear)	Thread (front)	Housing	Bolt-On Bit Body	Housing Lid	LidLock Pin	Lid Bolt	Torque Limit (ft.-lbs.)*
40,000 - 50,000	3.5"	2.375" IF	2.375" Reg	5735-HU4	5635-13, 5935-15	5735-HU4-CP	RP-038-200	SHCS1/2X3/4	Up to 4,568
50,000 - 80,000	4.25"	2.875" IF	2.875" Reg	5742-HU4	1742-23, 1942-25	5742-HU4-CP	RP-038-200	SHCS1/2X3/4	Up to 10,148
80,000 - 150,000	4.75"	3.5" IF	3.5" Reg	5747-HU4	3748-33	5742-HU4-CP	RP-038-200	SHCS1/2X3/4	Up to 13,879

*For each housing there are many drill rigs to choose from. The torque limitations are posed by the internal female threads found at the ends of each Large Universal Housing. Since each housing has two different sized female threads, the lowest torque limit from the two is shown for a conservative rating.



Patent-pending universal spacer allows you to secure models from separate manufacturers into a single housing pocket. Comes standard with all models of our Universal SD Housings.



THREE TRANSMITTER HOUSINGS IN ONE

- Compatible with 17" Subsite®, 15" & 19" DigiTrak™, and Underground Magnetics™ Transmitters
- Heat-treated, chrome-nickel-moly alloy material
- Large lid tabs for greater contact surface, reducing wear
- Compatible with Melfred Borzall's Eagle Claw SD, Iron Fist and Bolt-On Bit Bodies



Compatible with our thread-on SD Bit Bodies on page 8. See chart above for compatibility.